

THE 2100-SRT

STRETCH WRAP MACHINE

Carriage cable wires are not exposed

Load cell corner compensation for smooth and correct film dispensing

Includes safety door with auto power cut-off switch for safe and easy film threading.

Lifting tubes – front and rear for easy portability

Control panel with simple LCD operator interface including helpful diagnostics

All motors/gearboxes fully enclosed & guarded

All AC motors

4000# load capacity
Heavy-duty surround deck

BUILT IN NORTH AMERICA WITH BRAND NAME COMPONENTS.

THE 2100-SRT HAS FEATURES & BENEFITS THAT SURPASS THE COMPETITION

WHY THE THE 2100-SRT ?

◆ COMPACT

Affordable and simple with more standard features than any other pallet wrapper in this price range.

◆ ROBUST CONSTRUCTION

A quality machine built with quality components and supported by a local qualified distributor.

THE 2100-SRT

DESIGN FEATURES/SPECIFICATIONS

LOAD CAPACITY

- ◆ 50" L x 50" W x 80" H
- ◆ 4000# turntable capacity
- ◆ NOTE: Larger load size options are available.

CONTROLS

- ◆ LCD Operator Interface with Diagnostics
- ◆ Cycle Pause & Reinforce Wrap
- ◆ Separate UP/DOWN Spiral Speed Controls
- ◆ NEMA 12 with Emergency Stop Button
- ◆ 3 Separate Wrap Programs
- ◆ Selectable Reduced Film Tension parameters for wrapping top and/or bottom of light loads
- ◆ 115 Volts 1 Phase 60 Hz 15 Amps
- ◆ **3 Year Warranty on Components**

FILM CARRIAGE:

- ◆ Load Cell Film Delivery powered Pre-stretch film carriage
- ◆ Safety Door with auto power cut-off switch
- ◆ ½ HP AC variable speed motor
- ◆ 33% to 313% fixed stretch capability
- ◆ Carriage Descent Safety Shut-Off Device
- ◆ Superior film-to-roller contact area
- ◆ **Lifetime warranty on pre-stretch rollers**

TOWER DESIGN

- ◆ Fully Enclosed & Guarded Motors
- ◆ No Exposed Cables
- ◆ Heavy Duty Formed/Structural Steel
- ◆ Electro-static powder coated paint finish
- ◆ **5 Year Warranty on Steel Fabrications**

TURNTABLE

- ◆ 4000# capacity with Heavy Duty Surround deck
- ◆ 1 – 12 RPM with Soft Start Acceleration
- ◆ ½ HP AC Variable Speed Drive
- ◆ Forklift Tubes–Front and Rear
- ◆ Maintenance Free 42 Support Wheels
- ◆ 57" diameter
- ◆ Optional loading ramp 60" long x 48" wide complete with 10" level porch area available



Tap or scan the QR code to explore our solutions



OPTIONAL

Go Lite. Go Smart. *The next level is here!*



SMART TOUCH Lite

Wrap Programming

Production Data

Manual Controls

Data History

Diagnostics I/O