

MODEL 3300-CTA

Conveyorized Automatic

FILM TAIL TREATMENT - ALL ELECTRIC:

- ◆ Electric actuated film clamp mechanism
- ◆ Electro-mechanically actuated film tail cut/wiper arm mechanism
- ◆ Ni-chrome impulse hot wire film cut off c/w automatic periodic cleaning cycle



ALL ELECTRIC - no pneumatic lines or noisy air compressors required.

FILM CARRIAGE - Less film slippage means more consistent stretch and the "sticky" side of the film will always be against both the rubber rollers and the load where it belongs.



SYSTEM CONFIGURATION - Designed to be installed with existing product flow and conveyor layout design. Whether In-line or off-line, the automation package is designed to be in-line with conveyors using interface relays/logic or off-line standalone system using a wireless remote

MODEL 3300-CTA

DESIGN FEATURES/SPECIFICATIONS

PRODUCTION RATE

- ◆ Rated for 40 loads per hour depending on load sizes and number of wraps

LOAD CAPACITY

- ◆ 4000# Capacity
- ◆ 48" L x 48" W x 75" H max load size (24" minimum height)

NOTE: Larger load size options are available

CONVEYORS

- ◆ 2.5" diameter rollers on 3" centers
- ◆ 50" effective roller width –
- ◆ 16.5" standard passline height
- ◆ AC Drives

TOWER DESIGN:

- ◆ Fully Enclosed & Guarded Motors
- ◆ No Exposed Cables
- ◆ Heavy Duty Formed/Structural Steel
- ◆ Electro-static powder coated paint finish

5 Year Warranty on Steel Fabrications

FILM CARRIAGE:

- ◆ Super Rapid Thread II™ 20" capacity pre-stretch film carriage
- ◆ Special Film Threading Device – Uniquely orientates the sticky side of the film against the pre-stretch rollers and the inside on the load
- ◆ AC variable speed motor
- ◆ 33% to 313% fixed stretch capability
- ◆ Carriage Descent Safety Shut-Off Device
- ◆ Superior *film-to-roller* contact area

Lifetime warranty on pre-stretch rollers

CONTROLS

- ◆ LCD Operator Interface with Diagnostics
- ◆ Separate UP/DOWN Spiral Speed Controls
- ◆ 3 Separate Wrap Programs
- ◆ Selectable Reduced Film Tension parameters for wrapping top and/or bottom of light loads
- ◆ Emergency Stop button
- ◆ NEMA 12

3 Year Warranty on Components



The Association for Packaging and Processing Technologies



Tap or scan the QR code
to explore our solutions



CONTACT

TOLL FREE: 888-209-4344
INFO@COUSINSPACKAGING.COM
WWW.COUSINSPACKAGING.COM