

# THE 4100T Overhead (Rotary Arm) Semi-Automatic Series

CHOOSE A FRAME THAT FITS YOUR PRODUCTION SITUATION



4100-T-WM (Wall Mount)  
4100-T-PM (Post Mount)



Free-Standing 3 Post Stand



4100-T-FSR  
Rear Lag Down to Floor



4100H-FS  
Free-Standing 4 Post Stand

## ROBUST CONSTRUCTION

A quality machine built with quality components and supported by a local qualified distributor.

## COMPACT

Affordable and simple with more standard features than any other pallet wrapper in this price range



Tap or scan the QR code  
to explore our solutions



## CONTACT

TOLL FREE: 888-209-4344  
INFO@COUSINSPACKAGING.COM  
WWW.COUSINSPACKAGING.COM

# THE 4100-T & THE 4100-H

## DESIGN FEATURES/SPECIFICATIONS

### LOAD CAPACITY

- ◆ Unlimited load capacity
- ◆ **4100-T: 50" L X 50" W x 86" H max load size**
- ◆ **4100-H: 56" L X 56" W x 80" H max load size**
- ◆ NOTE: Larger load size options are available

### CONTROLS

- ◆ Panasonic PLC
- ◆ Separate UP/DOWN Spiral Speed Controls
- ◆ Emergency Stop Button
- ◆ Up Only or UP/DOWN wrap program
- ◆ Film Tension (Force-to-Load) control
- ◆ Rotary arm and film carriage elevator dynamic braking
- ◆ Triple beam type auto load height sensing photo-eye, detects dark or shiny loads
- ◆ Separate 1 to 9 revolution top & bottom wrap control
- ◆ NEMA 12 control panel enclosure
- ◆ 115 Volts 1 Phase 60 Hz 15 Amps
- ◆ **3 Year Warranty on Components**

### FILM CARRIAGE

- ◆ Super Rapid Thread II™ 20" capacity pre-stretch film carriage
- ◆ Safety Door with auto power cut-off switch
- ◆ Special Film Threading Device – Uniquely orientates the sticky side of the film against the pre-stretch rollers and the inside on the load.
- ◆ ½ HP DC variable speedmotor
- ◆ 33% to 313% fixed stretch capability
- ◆ Carriage Descent Safety Shut-Off Device
- ◆ Superior film-to-roller contact area
- ◆ **Lifetime warranty on pre-stretchrollers**

### ARM/TOWER DESIGN

- ◆ 4100-T
  - Double flange bearing support system
  - Twin V-Belt drive pulleys with belt tensioner
  - 1-12 RPM rotational speed c/w soft start acceleration
  - 1/2 HP DC variable speed motor
- ◆ 4100-H
  - Heavy duty ring bearing - chain/sprocket drive
  - 1 - 15 RPM
  - 3/4 HP DC variable speed motor
- ◆ Dust tight slip ring assembly
- ◆ Final revolution deceleration and positive stop alignment
- ◆ Heavy Duty Structural Steel
- ◆ Electro-static powder coated paint
- ◆ **5 Year Warranty on Steel Fabrications**

